

FACTORY FURNITURE



OSSO bench



Operation & Maintenance Manual

Factory Furniture Ltd | 5 Pioneer Road | Faringdon | Oxfordshire SN7 7BU | T +44 (0)1367 242731
hello@factoryfurniture.co.uk | www.factoryfurniture.co.uk

We reserve the right to change specification without notice. © 2017 Factory Furniture Ltd

A solid yellow horizontal bar spanning the width of the page at the bottom.

Introduction

Design

Design, shop drawings and development by Factory Furniture Ltd.

Manufacture

Factory Furniture manufactured components. Products are assembled in Factory workshops, checked and dispatched ready for installation. Replacement products or components thereof should be ordered direct from Factory Furniture Ltd.

Copyright

The design copyright for the product and drawing copyright remains the sole property of Factory Furniture Ltd.

General Specifications

Osso² Bench

Metric length 3950mm | width 700mm | height 470mm

Imperial length 12' 11½" | width 2' 3½" | height 1' 6½"

Approx Weight 148kg

Fixing Centres 2550mm (8' 4½") x 250mm (10")

Detailed Material & Finish Specifications

Main Body & Base Plates

- Manufactured from mild steel - hot dipped galvanised with polyester powder coat finish (powder coat colour - grey as standard or to customer specification)
- Base plates anchored to ground using 4 no. M12 x 90mm sleeve anchors per bench

General Maintenance *(Recommended Schedule & Guidelines)*

Daily/Weekly/Monthly *(or as adopted)*

Visual checks of bench - check for superficial or physical damage.

Three Monthly

Clean all items as detailed below check all fixings are seated correctly

Six Monthly

Secure all fixings; full clean as detailed below; check that bench is firmly secured to the ground

Specific Maintenance Details

Polyester Powder Coated & Galvanised

For general cleaning using a damp cloth and warm soapy water only. Scourers and abrasive cleaners are NOT suitable for this type of finish and may damage it. Before using any cleaning agents to remove graffiti etc. try on a small, inconspicuous area first to avoid causing more unsightly damage

Repairs

Polyester Powder Coated & Galvanised Surfaces

For light damage (scratches, chips etc.) repair using touch-up paint to match original colour (available from Factory Furniture Ltd). Paint application should be carried out in accordance with approved methods detailed by the paint manufacturer. Please note that it is advisable to use professional painters to achieve best results when touching up larger areas. Products for respraying larger areas are available from Factory Furniture Ltd.

Heavy Damage

In the event of serious damage to any component, replacements should be ordered from Factory Furniture Ltd. In this event (or if the product needs to be disassembled for any reason), please contact Factory Furniture for detailed technical advice

AutoCAD Drawing List

FF1039 / 01	OSSO BENCH	GENERAL ARRANGEMENT DRAWING
FF1039 / 02	OSSO BENCH	PART DETAIL DRAWINGS (MAIN BODY)
FF1039 / 03	OSSO BENCH	PART DETAIL DRAWINGS (BASE)
FF1039 / 04	OSSO BENCH	SETTING OUT DRAWINGS


Contacts

Factory Furniture Ltd,
5 Pioneer Road
Faringdon
Oxfordshire
SN7 7BU
UK

Tel +44 (0) 1367 242731
Email hello@factoryfurniture.co.uk
Web www.factoryfurniture.co.uk

Installation Instructions

ALL INSTALLATION WORKS TO BE CARRIED OUT BY COMPETENT PERSONNEL - INSTALL AS COMPLETE UNIT



Osso Bench (surface fix only)

1. Install suitable foundation pads (see illustration) each with top face at ground level
2. Position bench in correct orientation with bases centrally on foundation pads, then mark hole positions through base plates
3. Remove the bench; drill holes $\text{Ø}20\text{mm} \times 90\text{mm}$ deep (or as bolt manufacturer's recommendations)
4. Clear debris from holes
5. Reposition bench and fix to foundation pads using 4 no. zinc-coated M12 x 90mm sleeve anchors tightened to 50Nm (or as per manufacturer's instruction).
6. Check levels

